

MATERIAL SAFETY DATA SHEET

NAME OF PRODUCT

MSDS DATE: 03/20/09

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 661F 60-Day Air Freshener Cartridge - Floral
SYNONYMS:
PRODUCT CODES:

MANUFACTURD FOR: Impact Products, LLC
ADDRESS: 2840 Centennial Road, Toledo, OH 43617

EMERGENCY PHONE: 800-228-5635 Ext. 167
CHEMTREC PHONE: 800-424-9300
DOT EMERGENCY (INT'L): 703-527-3887
OTHER INFORMATION: 800-796-5573

CHEMICAL NAME:
CHEMICAL FAMILY:
CHEMICAL FORMULA:

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT:	CAS NO.	% WT	TLV/PEL
Isobutylacetate	110-19-0	.83	OSHA PEL: 150 ppm ACGIH TLV: 150 ppm

Notes: The following information only applies when a number appears in the right hand note column.

1. PEL/TLV not established for this material.
2. This chemical is listed as a toxic chemical subject to the SARA 313 (Superfund amendments & Reauthorization Act of (1986) toxic chemical release reporting requirement.
3. This chemical is considered a carcinogen by the OSHA , NTP, or the IARC

Any hazardous component is subject to the reporting requirements for Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

SECTION 3: HAZARDS IDENTIFICATION

ROUTES OF ENTRY: Eyes - Yes Skin - Yes Inhalation - Yes Ingestion - Yes

POTENTIAL HEALTH EFFECTS

EYES: May cause eye irritation by direct contact or by fumes
SKIN: Prolonged contact may lead to irritation or dermatitis
INGESTION: May cause respiratory tract irritation
INHALATION: Harmful if swallowed
ACUTE/CHRONIC HEALTH HAZARDS:
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

CARCINOGENICITY

OSHA: No NTP: No IARC: No OTHER:

SECTION 4: FIRST AID MEASURES

EYES: Flush eyes with water for at least 15 minutes. If irritation persists, contact a physician
SKIN: Wash skin with soap and plenty of water. Remove contaminated clothing and wash before wearing again
INGESTION: If swallowed, drink milk or water and contact a doctor immediately
INHALATION: Remove victim to fresh air

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS: LEL - n/a UEL - n/a
FLASH POINT: 185 degrees F

METHOD USED:

HMIS HAZARD CLASSIFICATION: HEALTH - 1 FLAMMABILITY - 2 REACTIVITY - 0

EXTINGUISHING MEDIA: Carbon dioxide, dry chemical, universal-type foam

SPECIAL FIRE FIGHTING PROCEDURES: Standard fire-fighting procedures may be followed, including full protective gear, NIOSH approved self-contained breathing apparatus if needed

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers may build up pressure at elevated temperatures. If possible, containers should be cooled with a water spray

MATERIAL SAFETY DATA SHEET

NAME OF PRODUCT

MSDS DATE: 03/20/09

SECTION 13: DISPOSAL CONSIDERATIONS/PROCEDURES FOR SPILL OR LEAK CLEANUP

WASTE DISPOSAL METHOD: Incinerate, bury in approved manner or dispose in accordance with local, state, and federal regulations.

PROCEDURE FOR SPILL OR LEAK CLEANUP: Avoid sources of ignition. Contain spilled material. Avoid inhalation of vapors. Cover with a non-combustible material and remove to an approved disposal container. Dry products should be swept up and removed to an approved disposal container. Wash area with soap water.

SECTION 14: TRANSPORT INFORMATION

Follow state and federal regulations.

SECTION 15: REGULATORY INFORMATION

Follow state and federal regulations.

SECTION 16: OTHER INFORMATION

OTHER INFORMATION:

DISCLAIMER: The information furnished herein is believed to be accurate and represents the best data currently available to us. No warranty, expressed or implied is made and Impact Products LLC assumes no legal responsibility or liability resulting from its use.